

201-15005A

High Production Volume Challenge

Test Plan

for

Acetylene
CAS No. 74-86-2

RECEIVED
COPY 0110
04 JAN -6 PM 3:00

Prepared by:

American Chemistry Council
Acetylene Panel

December 30, 2003

TABLE OF CONTENTS

1.0	Introduction.....	3
2.0	Designation of Test Substance.....	3
3.0	Criteria for Determining Adequacy of Data	4
4.0	Available Data	4
4.1	Chemical and Physical Properties	5
4.1.1	Melting Point	5
4.1.2	Boiling Point	5
4.1.3	Vapor Pressure	5
4.1.4	Octanol/Water Partition Coefficient	5
4.1.5	Water Solubility.....	5
4.1.6	Explosivity	5
4.1.7	Summary/Test Plan for Physical Properties	5
4.2	Environmental Fate/Pathways	6
4.2.1	Photodegradation.....	6
4.2.2	Stability in Water.....	6
4.2.3	Fugacity	6
4.2.4	Biodegradation.....	7
4.2.5	Summary/Test Plan for Environmental Fate Parameters.....	7
4.3	Aquatic Ecotoxicity	8
4.3.1	Acute Toxicity to Fish.....	8
4.3.2	Acute Toxicity to Aquatic Invertebrates.....	8
4.3.3	Acute Toxicity to Aquatic Plants.....	8
4.3.4	Summary/Test Plan for Ecotoxicity.....	9
4.4	Human Health Data	9
4.4.1	Acute Mammalian Toxicity.....	9
4.4.3	Genetic Toxicity	11
4.4.3.1	Mutagenicity	11
4.4.3.2	Chromosomal Aberration	11
4.4.4	Reproductive and Developmental Toxicity.....	11
4.4.5	Other Health Information	12
4.4.6	Summary/Test Plan for Mammalian Toxicity.....	14
5.0	Summary.....	15
6.0	References.....	17

LIST OF TABLES

Table 1. Chemical/physical Properties of Acetylene and Methylacetylene	6
Table 2. Environmental Fate Parameters for Acetylene	7
Table 3. Ecotoxicity of Acetylene	8
Table 4. Test Conditions and Results for Franklin and Miklos Study (1933)	10
Table 5. Summary of Data Availability for Acetylene (CAS No. 74-86-2).....	16


1.0 Introduction

The Acetylene Panel¹ (Panel) of the American Chemistry Council (ACC) has agreed to supply screening level hazard and use information under the U.S. EPA High Production Volume (HPV) Challenge Program for acetylene (CAS No. 74-86-2). This plan identifies existing data of adequate quality for this chemical, and how the data serve to address the HPV Challenge screening endpoints.

2.0 Designation of Test Substance

Test Substance

The test substance presented in this test plan is acetylene (CAS No. 74-86-2). Its molecular structure is as follows:



Acetylene is a well-known industrial gas. It is the lowest molecular weight analog of the class of neutral organic, acetylenic compounds. This substance is also known as ethyne.

Nearest Analog

The next higher homolog (nearest analog) of acetylene is methylacetylene (CAS No. 74-99-7), also known as propyne or 1-propyne. Its molecular structure is as follows:



Data for methylacetylene will be used to address the repeat dose and bacterial reverse mutation assay endpoints for acetylene in this test plan. Information for methylacetylene should be predictive of acetylene for the following reasons:

- Methylacetylene, as the next higher acetylenic homolog, is the most closely related chemical to acetylene in molecular structure and size, and has the identical functionality (the carbon-carbon triple bond);
- Methylacetylene, also a gas at ambient temperatures, exhibits physical/chemical properties that are similar to acetylene, as shown in Table 1; and
- The acute toxicity of methylacetylene in mammals is closely similar to that of acetylene.

The reasons for choosing methylacetylene are consistent with the EPA draft guidance for “The Use of Structure- Activity Relationships (SAR) in the High Production Volume Chemicals Challenge Program.” Based on a review of the data, it is concluded that methylacetylene is a valid analog for acetylene and that the uptake, metabolism, ecotoxicology and health effects of the two compounds is

¹ The current members of the Acetylene Panel are: Air Liquide America Company; BASF Corporation; Chevron Phillips Chemical Company; Dow; DuPont; Equistar Chemicals, LP; Praxair, Inc.; Rohm and Haas Company; and Shell Chemicals Limited.

expected to be very similar. Therefore, data comparison is used for those instances where valid and reliable data are available for methylacetylene but not for acetylene.

Manufacture of Acetylene

In the United States, seven companies currently manufacture acetylene for use primarily as a chemical intermediate that is used in closed systems. U.S. manufacturing capacity in 2001 totaled 333 million pounds (Laeson et al., 2001). This capacity included both captive and merchant capabilities, but did not include smaller amounts made by industrial gas producers for use in acetylene torches.

The major producers in the U.S. manufacture acetylene by either the partial oxidation of natural gas or as a co-product from the steam cracking of ethylene (Kirk-Othmer, 1995). Acetylene produced by either method is used primarily as a closed system industrial intermediate. Minor producers manufacture smaller amounts of acetylene by reacting calcium carbide with water manufactured using the carbide process. This acetylene is used primarily in acetylene torches.

Uses of acetylene

In the year 2000, approximately 80% of U.S. production was used as a closed system industrial intermediate in the synthesis of other chemicals (Laeson et al., 2001). The remaining 20% of production was predominantly used in oxyacetylene torches for welding and metal cutting (Laeson et al., 2001). Currently, 96% of manufacturing capacity of the 7 major manufacturers is slated for use as a closed system industrial intermediate. Most of this use occurs at the manufacturing sites, because of the economic and physical impracticality of transferring large quantities of acetylene gas to other sites. Some acetylene is also transferred through pipes to neighboring facilities for conversion to other products. Products made from acetylene include vinyl chloride monomer, acetylene black, vinyl fluoride, N-vinylcarbazole, N-vinylcaprolactam and other derivatives such as 1,4-butanediol, vinyl ethers, N-vinyl-2-pyrrolidone, and vinyl esters. Acetylene was used in the early 1900's as an anesthetic (under the name Narcylene). It is no longer used as an anesthetic because better, less explosive alternatives are available. No uses of acetylene in consumer products are known. Since the majority of acetylene is used as a closed system industrial intermediate and as a fuel for oxyacetylene torches, minimal occupational exposure, with no consumer exposure, is expected.

3.0 Criteria for Determining Adequacy of Data

All identified available studies were reviewed and assessed for adequacy according to the standards of Klimisch et al. (1997). Studies receiving a Klimisch rating of 1 or 2 are considered to be adequate.

4.0 Available Data

The summary of available data for acetylene (as shown in Table 5) was constructed after a careful evaluation of all identified existing data (see below).

4.1 Chemical and Physical Properties

Key chemical/physical properties of acetylene and methylacetylene are discussed in the following sections and summarized in Table 1.

4.1.1 Melting Point

A melting point of -80.8°C for acetylene is reported by Lide (1992-1993). The same reference cites a melting point of -101.5°C for methylacetylene.

4.1.2 Boiling Point

A boiling point of -84°C is reported for acetylene by Lide (1992-1993). The same reference cites a melting point of -23.2°C for methylacetylene.

4.1.3 Vapor Pressure

A vapor pressure of 6,969.2 hPa is reported for acetylene by Daubert and Danner (1989). This value was calculated from experimentally derived coefficients. The vapor pressure of methylacetylene is 5,155 hPa (Clayton and Clayton, 1981-2).

4.1.4 Octanol/Water Partition Coefficient

The method of Hansch and Leo (1995) was used to estimate a log Kow of 0.37. The same method was used to estimate a log Kow of 0.94 for methylacetylene.

4.1.5 Water Solubility

A measured water solubility of 1,230 mg/l at 1,010 hPa and 20°C is cited in Grayson (1978). This value is consistent with the water solubility value of 1,200 mg/l reported in the Hazardous Substances Data Bank (2003). These values indicate that acetylene theoretically has appreciable water solubility. However, the likelihood that acetylene concentrations in water would ever approach this level (except under controlled or forced conditions) is remote based on its very strong tendency to volatilize to its normal gaseous state (See Table 2 and Section 4.2.3). The water solubility of methylacetylene is reported to be 3,640 mg/l (McAuliffe, 1966).

4.1.6 Explosivity

Acetylene is a gas that forms highly explosive mixtures in air across a broad range of concentrations. The lower explosive limit (LEL) is 2.5% (25,000 ppm) in air (National Fire Protection Association, 1997).

4.1.7 Summary/Test Plan for Physical Properties

Acetylene has been a commercial industrial chemical for many decades, and its key physical properties are well established. Although the data were determined long ago (and therefore not generated using current guideline methods), the data should be accepted as reliable. Measured data are available for many of the required physical property endpoints. The melting and boiling points are -80.8°C and -84°C, respectively. The calculated vapor pressure is 6,969.2 hPa at 25°C. The

estimated octanol/water partition coefficient is 0.37. Based on its very high vapor pressure, both the estimated partition coefficient and the appreciable water solubility of 1,200 mg/l are largely of only theoretical relevance. No new testing for physical properties is proposed.

Table 1 shows the comparison of physical properties for acetylene and the nearest analog, methylacetylene. The similarities of these properties are noted.

Table 1. Chemical/physical Properties of Acetylene and Methylacetylene

<i>Endpoint</i>	<i>Acetylene</i>	<i>Methylacetylene</i>
Molecular weight (grams/mol)	26.04	40.07
Melting point	-80.8°C ^a	-101.5°C ^a
Boiling point (at 1016 hPa)	-84 °C ^a	-23.2°C ^a
Relative density (at -82°C)	0.6208 ^a	0.7062 ^a
Vapor pressure (hPa)	6,969.2 ^b (at 25° C)	5,155 ^a (at 20° C)
Partition coefficient (Log Pow or Kow)	0.37 ^b	0.94 ^b
Water solubility (mg/l at 25 ° C)	1,230 ^a	3,640 ^a

^a Measured value; ^b Estimated value

4.2 Environmental Fate/Pathways

The results of environmental fate modeling and studies are discussed below and summarized in Table 2.

4.2.1 Photodegradation

Photodegradation with hydroxyl radical sensitizer was estimated using EPIWIN/Aop (v1.90). An overall hydroxyl radical rate constant of $8.15 \times 10^{-13} \text{ cm}^3/(\text{molecule} \cdot \text{sec})$ was calculated based on the summation of individual rate constants for each bond fragment in the molecule using the program algorithm. A half-life of 13.1 days was calculated assuming a constant concentration of OH radical and pseudo first order kinetics. Since acetylene is a gas (except at temperatures well below 0°C), atmospheric photodegradation is expected to be the most significant route of degradation in the environment.

4.2.2 Stability in Water

Because the material is a gas, rapid volatilization is by far the relevant environmental fate pathway for acetylene in the hydrosphere. Therefore, it is not necessary to conduct experiments to determine water stability. Since acetylene does not contain functional groups that are known to be readily hydrolyzed (i.e., ester groups, nitriles, amides, etc.), it is not expected to hydrolyze readily under neutral ambient conditions. The carbon-carbon triple bond is generally recognized to be stable in water. Therefore, the small amount of material that may be present in the hydrosphere is expected to remain intact until it evaporates.

4.2.3 Fugacity

Level III fugacity modeling has been conducted on acetylene using the EPIWIN model. Inputs to the program were CAS No. 74-86-2, a melting point of -80.8 °C, a boiling point of -84°C, a vapor pressure of 6,969.2 hPa and water solubility of 1,200 mg/l. The emission rate inputted into the program for air was 1,000 kg/hr (model default value). The emission rates inputted to water, soil and sediment were 0 kg/hour. These emission rates are more in keeping with manufacturing and use processes that are extremely unlikely to emit significant emissions to these media, and forcing acetylene into these media would be very difficult based on the physical properties of acetylene. Model default emissions of 1,000 kg/hr (87,600,000 kg/year) to the air are beyond reasonable worst-case assumptions, especially from point sources. The following half-lives were calculated: $T_{1/2\text{air}} = 298$ hrs, water = 360 hrs, soil = 360 hrs, and sediment = 1,440 hrs. A Henry's Law Constant of 0.024 atm-m³/mol and a soil sediment partition constant (K_{oc}) of 14.3 were estimated using the EPIWIN/Henry and PCKOC Programs, respectively. The percent mass balances predicted for acetylene in air, water, soil and sediment are shown in Table 3. The results show that 99.9% of acetylene will remain in the atmosphere after being discharged into it.

4.2.4 Biodegradation

Since acetylene is a gas and 99.9% partitions to the air according to the Fugacity Level III model, biodegradation is not an important route for removal of the material from the environment. Furthermore, since standard OECD biodegradation tests are not designed to assess the relative biodegradability of gaseous materials, such tests will be difficult to perform and will not adequately assess the ability of the material to biodegrade in the environment. Since the material is a gas, the primary means of degradation of the vast majority of the material in the environment is photodegradation, which supports the conclusion that biodegradation is irrelevant.

4.2.5 Summary/Test Plan for Environmental Fate Parameters

Estimated values are available for the hydroxyl radical induced photolysis rate constant and atmospheric half-life, Henry's Law Constant and Fugacity Level III environmental transport parameters. These values indicate that acetylene has a very strong tendency to partition to the atmosphere, where it undergoes photodegradation. Standard biodegradation tests have not been performed with acetylene and are not considered relevant studies to conduct on a gas that will mainly partition to air. Although the material is expected to be stable in water, any material present in water will rapidly evaporate. Therefore, no testing for water stability (hydrolysis) is proposed.

Table 2. Environmental Fate Parameters for Acetylene

<i>Endpoint</i>	<i>Value</i>
Indirect Photolysis (OH sensitizer) (Hydroxyl Radical Rate Constant) ^a (Atmospheric $T_{1/2}$) ^a	8.15 E-13 cm ³ /molecule-sec 13.1 days
Stability in Water	Should not hydrolyze
Henry's Law Constant ^a	0.024 atm-m ³ /mol
Environmental transport (Fugacity Level III mass percentages) ^a	Air = 99.9 Water = 0.104 Soil = 0.0101 Sediment = 0.000177
Biodegradation	Not applicable

^a Estimated using EPIWIN

4.3 Aquatic Ecotoxicity

Since acetylene is a gas that will partition to air and rapidly evaporate from the aqueous environment, ecotoxicity testing is not considered relevant. Nonetheless, some toxicity tests have been conducted in several aquatic species. The results of this testing (along with ECOSAR modeling) are discussed below and summarized in Table 3.

Table 3. Ecotoxicity of Acetylene

<i>Species</i>	<i>LC50/EC50 (mg/l) (time)</i>
Fish (unspecified)	approx. 500 ^a (96 hour)
Lepomis sp.	> 1,000 (1 hour) ^b
Minnow (unspecified)	> 17 (1 hour) ^b
Trout fingerlings	200 (33 hour) (limit of toxicity) ^b
Cyprinus auratus (goldfish)	400 (24-48 hour) (limit of toxicity) ^b
Fingerling chinook salmon	3,500 (72 hours) (limit of toxicity)
Young rainbow trout	3,000 – 5,000 (72 hours) (limit of toxicity)
Daphnia magna	approx. 480 ^a (48 hour)
Green algae	approx. 275 ^a (96 hour)

^a Estimated using EPIWIN; ^b Given a reliability rating of 4 due to lack of information

Since experimental conditions were not listed and the primary references were not available for the fish toxicity studies, it is not known whether the concentrations listed are nominal or measured, or if the studies were conducted using flow through or static methods. If the experiments were performed using closed systems that would force acetylene into the water and minimize volatilization, the relevance of the results for the aquatic environment would be questionable. Such attempts would eliminate airspace around the liquid and lead to deoxygenation. In conclusion, the testing and modeling that have been done are adequate for HPV purposes. No additional testing is proposed.

4.3.1 Acute Toxicity to Fish

The 96-hr LC50 value for fish estimated by EPA's ECOSAR model for the neutral organic class is approximately 500 mg/l. This is similar to concentrations reported as causing death to an unknown number of trout fingerlings and goldfish in the OHM/TADS database, and less than concentrations reported to cause toxicity in fingerling chinook salmon and young rainbow trout. The concentrations reported for salmon and rainbow trout (3,500 and 3,000-5,000 mg/l respectively) are suspect, since, these values exceed the measured water solubility of acetylene. Since references for these studies were not given in the database and were not available, they could not be reviewed. Therefore, reliability ratings of 4 (not assignable) were designated for these studies.

4.3.2 Acute Toxicity to Aquatic Invertebrates

EPA's ECOSAR model for the neutral organic class predicts a 48-hour EC50 value of approximately 480 mg/l for *Daphnia*. No experimental test data were available.

4.3.3 Acute Toxicity to Aquatic Plants

The 96-hr EC50 value calculated for green algae by the ECOSAR model for the neutral organic class is approximately 275 mg/l. No experimental test data were available.

4.3.4 Summary/Test Plan for Ecotoxicity

The available ecotoxicity data, combined with the ECOSAR results, adequately address the ecotoxicity endpoints for HPV purposes. Since the material is a gas, it will evaporate quickly from water. Tests that are performed in closed systems in the laboratory will not adequately simulate environmental conditions in which acetylene will remain in the atmosphere. Experimental studies performed to prevent volatilization may also be accompanied by deoxygenation, which is not expected to actually occur in environmental bodies of water. In the aqueous environment, acetylene should not be present at concentrations estimated by ECOSAR to cause toxicity to aquatic species. No additional ecotoxicity testing is proposed.

4.4 Human Health Data

Because acetylene is a gas, it is not relevant to test the material using oral or dermal routes of application. Inhalation is the only significant potential route of exposure.

4.4.1 Acute Mammalian Toxicity

With decades of production and use, the acute toxicity of acetylene is well understood to be that of a simple asphyxiant. Data regarding the acute inhalation toxicity to animals and humans clearly show that acetylene is of a very low acute toxicity. Overall, the data support a rat LC50 > 100,000 ppm.

In humans, acetylene is not acutely toxic below its lower explosive limit of 2.5% (25,000 ppm). Inhalation of 10% acetylene (100,000 ppm) for 1 hour does not cause acute toxicity. Inhalation of 33% or 35% has caused unconsciousness within 7 and 5 minutes, respectively (Davidson, 1925). Two deaths and a near fatality occurred after inhalation of 40% acetylene during manufacture with calcium carbide (Carreñ, 2000; Jones, 1960). The cause of these deaths was attributed to the phosphate and arsine impurities in crude acetylene and carbon monoxide present in the work area.

In rats, a concentration of 78% acetylene (780,000 ppm) produced anesthesia in 15 minutes, and inhalation of 90% for 2 hours caused respiratory failure (Riggs, 1925). Inhalation of 850,000 ppm caused increased respiratory volume and frequency and induced anesthesia in dogs, with rapid recovery (Heymans and Bouckaert, 1925). Therefore, the LC50 value in this study was greater than 850,000 ppm.

4.4.2 Repeated Dose Mammalian Toxicity

In 1933, Franken and Miklos looked for possible organ damage from the administration of acetylene at anesthetic concentrations to rats, mice, guinea pigs, rabbits, and dogs. Animals were exposed to acetylene in oxygen according to the scheme presented in Table 4.

Table 4. Test Conditions and Results for Franklin and Miklos Study (1933)

<i>Animal</i>	<i>Number Tested</i>	<i>Conc. (%)</i>	<i>Daily Exposure Time (hours)</i>	<i>Number Of Days Exposed</i>	<i>Total Exposure Time (hours)</i>	<i>Deaths</i>
Rat	16	25	1	7-93	7-93	6
Rat	10	50	2	1-8	2-16	9
Guinea Pig	7	50	2	1-9	2-18	7
Mouse	5	50	2	1-6	2-12	5
Rat	47	80	½	2-36	1-18	36
Rat	8	80	1	14	14	0
Guinea Pig	6	80	1	10	10	0
Rabbit	4	80	1	6-10	6-10	3
Dog	2	80	1	12	12	1

At the lower concentrations (concentrations were not stated) the animals appeared only slightly sleepy. At higher concentrations the majority of animals fell asleep after 15-20 minutes. In general, these animals were not in deep narcosis. The rats, rabbits, guinea pigs and dogs generally recovered from narcosis in a short time. However, the mice did not survive treatment. Some of the animals died spontaneously. Pneumonia was observed in most of these cases. Since pneumonia also was observed in control animals exposed only to air, it does not appear to be related to treatment. In treated animals that survived to termination, the authors found no evidence of cellular injury to the parenchymatous cells of the heart, lungs, liver, kidneys, or spleen. However, capillary hyperemia of the liver, kidneys and spleen was observed in some rats exposed to 25%. This effect was observed until at least the second day after the last exposure to the gas but was not evident in animals killed later (up to 5 days after the last exposure). Since capillary hyperemia was not observed in rats exposed to higher concentrations of acetylene, it does not appear to be test-material related. In conclusion, since repeated exposure of rats to a concentration (25%) that greatly exceeds any concentration that would be expected to occur in routine human working conditions did not cause any organ toxicity, it is expected that repeated exposure of humans to concentrations routinely encountered in the workplace would not cause organ toxicity.

The repeated dose toxicity of the analog methylacetylene has been studied in rats and dogs (Horn et al., 1957). In this study, the animals were exposed to 28,700 ppm methylacetylene 6 hr/day, 5 days/week for 6 months. Rats and dogs reached an early plane of anesthesia (within 30 minutes) and generally recovered rapidly after each exposure. Forty percent of the rats and none of the dogs died over the course of the study. Gross pathology of the rats that died was limited to the lungs, which appeared dark red and remained distended when the thorax was opened. In exposed rats that survived to termination, the lungs also were discolored and remained distended. Microscopic pathology of the lungs showed definite pulmonary irritation. The remaining organs appeared to be within normal limits. There was no effect of treatment on any hematological, urine or biochemical index of toxicity in the dogs. The gross appearance of all organs examined and microscopic examinations of the lung, liver, kidney, heart, spleen and GI tract in exposed dogs were normal. Overall, the authors of the study concluded that methylacetylene is of low repeated dose toxicity and the site of toxicity was limited to the lungs, even at extremely high concentrations (28,700 ppm).

4.4.3 Genetic Toxicity

4.4.3.1 Mutagenicity

In an Ames test employing three strains of *S. typhimurium* (TA97, TA98, TA100), acetylene did not induce mutations in both the absence and presence of metabolic activation (Hughes et al., 1984). This test was given a reliability rating of 2 (valid with restrictions), since current guidelines recommend testing in 4 different *S. typhimurium* strains and a strain of *E. coli*.

In a more recent test conducted in *S. typhimurium* TA98, TA100, TA1535 and TA1537 and *E. coli* WP2uvrA, the related material methylacetylene did not cause an increase in mutations in any strain of Salmonella at any concentration in the absence or presence of metabolic activation (Araki et al., 1994). However, there was a dose dependent increase in the number of mutations in *E. coli* WP2 uvrA in the absence or presence of metabolic activation.

Overall, the weight-of-evidence on acetylene and its surrogate (methylacetylene) indicate that acetylene is not mutagenic.

4.4.3.2 Chromosomal Aberration

No chromosome aberration tests were identified for acetylene or methylacetylene. Available information suggests, however, that exposure to acetylene would not result in chromosomal damage. This endpoint is considered fulfilled for HPV purposes and it is deemed not appropriate or relevant to conduct new testing for the following reasons, discussed in further detail in Section 4.4.4:

- The American Conference of Governmental Industrial Hygienists (ACIGH) Threshold Limit Value (TLV) Committee did not consider acetylene to be of reproductive concern when establishing a TLV, which is based on acetylene being a simple asphyxiant;
- As acetylene is used primarily as a closed system industrial intermediate, or as a welding gas where it is combusted, there is only a remote likelihood that human beings can be exposed to meaningful concentrations of acetylene, even in the workplace;
- Acetylene has been used for over 100 years as an anesthetic and industrial chemical and during this time period no link between genetic toxicity and the use of acetylene has been established; and
- A high fire and explosion hazard would be associated with any testing at meaningful concentrations.

4.4.4 Reproductive and Developmental Toxicity

No adequate reproductive or developmental toxicity studies have been located for acetylene. It is not deemed appropriate or relevant to conduct new testing for these endpoints for these reasons (which are discussed in greater detail below):

- The American Conference of Governmental Industrial Hygienists (ACIGH) Threshold Limit Value (TLV) Committee did not consider acetylene to be of reproductive concern when establishing a TLV, which is based on acetylene being a simple asphyxiant;

- As acetylene is used primarily as a closed system industrial intermediate, or as a welding gas where it is combusted, there is only a remote likelihood that human beings can be exposed to meaningful concentrations of acetylene, even in the workplace;
- It has been demonstrated that acetylene is minimally toxic to mammals, except at exceedingly high doses. The repeated dose study on the acetylene surrogate methylacetylene indicated effects only at the site of administration (lungs), and no effects at other organs. Evidence indicates that mammals do not metabolize acetylene but instead eliminate acetylene rapidly and unchanged from the lungs. Reproductive and developmental effects are not likely to occur as they would be effects that are remote to the lungs;
- Acetylene has been used for over 100 years as an anesthetic and industrial chemical and during this time period no link between any reproductive or developmental effect and the use of acetylene has been established; and
- A high fire and explosion hazard would be associated with any testing at meaningful concentrations.

These reasons are discussed in further detail below.

4.4.5 Other Health Information

ACGIH Classifies Acetylene as a Simple Asphyxiant

The ACGIH has reviewed the toxicology of acetylene and found no reason to assign a TLV for the workplace, giving acetylene a simple designation as an asphyxiant (ACGIH, 2003).

Inability to Expose Workers or General Population to Meaningful Concentrations of Acetylene

Approximately 80% of acetylene produced is used as a closed system industrial intermediate to manufacture other chemicals. Much of this use is at the same site as manufacture, with the acetylene being transferred from the closed manufacturing and storage units to the conversion units via pipes. The other primary use (approximately 20% of production) is in oxyacetylene torches for welding and metal cutting where mixtures of acetylene/air or acetylene/oxygen mixtures are burned to provide a very high temperature heat source. In this operation, acetylene gas is released from closed cylinders through a nozzle jet that is ignited to form the hot flame. In welding, acetylene undergoes essentially complete combustion in the process. Acetylene is contained in enclosed equipment during manufacture, storage, transport and use. Acetylene is not believed to be present in consumer products. While it is possible that acetylene gas could escape from gas cylinders, enclosed reactors, pipes and storage tanks, such escape would be a result of a non-routine, emergency circumstance, such as a line rupture or failed valve. In such cases, immediate action is required to prevent escape of significant quantities, since just 2.5% or greater concentrations in air form explosive and combustible mixtures that are given the highest flammability hazard ratings. Therefore, air concentrations must be held to much lower levels, and work areas must be evacuated if significant air concentrations start to develop via accidental release. In summary, the most meaningful hazard associated with acetylene is fire and explosion that would be life-threatening before toxicological hazards could develop.

Simple diffusion model calculations show maximum expected 1-hour average ambient concentrations at approximately 5.5 ppm, and at approximately 3 ppm for 24-hour values of acetylene near a plant boundary. Urban concentrations of approximately 80 ppb and rural values of 1 ppb have been measured. Based on the “low toxicity and expected low ambient concentrations, acetylene does not pose a health or environmental hazard as an air pollutant” (Patterson et al., 1976).

Demonstrated Minimal Toxicity

Acetylene is not acutely toxic below its lower explosive limit of 2.5% (25,000 ppm). It has been well established that acetylene behaves in mammalian systems primarily as a central nervous depressant and asphyxiant at high dose levels (100,000 ppm in air or above). It produces varying degrees of temporary and reversible narcosis when administered with oxygen in concentrations of $\geq 100,000$ ppm (10% in air). Repeated exposure of rats, mice, guinea pigs rabbits and dogs to concentrations $\leq 800,000$ ppm showed no evidence of cellular injury to the parenchymatous cells of the heart, lungs, liver, kidneys, or spleen (Franklin and Miklos, 1933). The only histologic findings in rats exposed an anesthetic concentration (28,700 ppm) of the related material methylacetylene for 90 days were confined to the lungs (Horn et al., 1957).

Limited data reported in the literature indicate that acetylene is rapidly absorbed and eliminated unchanged in the body (Adriani, 1952, 1962). The blood-gas partition coefficient of acetylene at normal hematocrit and body temperature is 0.833 (Jibelian et al., 1981), indicating that the material has a greater propensity to be removed from blood than to be retained in it. Schrikker et al. (1989) have shown that, in man at rest, the rates of alveolar and mixed venous washout for acetylene calculated from the slopes of the of the alveolar plateau are 2.6% and 4.8% per second, respectively. Within 10 minutes of inhalation of acetylene for 15 minutes, the end tidal concentration was 8.0 % of its initial value. Together, these data support the contention that the lungs rapidly excrete acetylene. The gas also diffuses rapidly from the peritoneal and pleural cavities and diffuses through the skin. Therefore, acetylene is unlikely to persist in the body, even after repeated exposure to low concentrations that may be encountered in the workplace.

Long History of Use

Acetylene has been used for over 100 years as an anesthetic and industrial chemical, and few complications of using this gas have surfaced. According to the Hazardtext database, “there is no scientific evidence that repeated exposure to tolerable levels of acetylene leads to deleterious health effects.” Epidemiological studies that have been published have failed to establish a link between use of acetylene and cancer. Exposure to acetylene is not associated with liver angiosarcoma in workers exposed to a number of materials (Waxweiler, 1981). Acetylene exposure also was not a risk factor in mortality from lung cancer in a case-referent study in which exposure to chemicals in an acetylene and phthalic anhydride plant accounted for one third of the total number of lung cancer deaths (Riboli et al., 1988). In a pilot study conducted on 454 men, no associations were found between occupational exposure to acetylene and development of cancer (Siemiatycki et al., 1982). In a study conducted on 370 workers involved in acetylene cylinder manufacture between 1935 - 1975, an excess of deaths from lung cancer, and cancer of the stomach and pancreas was observed. However, an association between exposure to acetylene and lung cancer was not identified (Newhouse et al., 1988). Acetylene also was not listed as a risk factor for developing cancer in a study involving 632 Danish male molders (Hansen, 1991). In two case-controlled studies, acetylene exposure was not identified as a risk factor for developing multiple myeloma (Morris et al., 1986; Williams et al., 1989). In a Texas plant, which utilizes acetylene and other chemicals to produce

acrylate and methacrylate ester, the excess of total cancer deaths in those hired from 1958 to 1962 could not be correlated with job-related causes (Rohm and Haas, 1980).

In an epidemiological study conducted in Russia, the health status of an unknown number of pregnant women chemists who produced acetylene-vinyl acetate from 1972-1975 was compared to that of 84 pregnant women that did not work with chemicals (Talakina et al., 1977). Twenty percent of the chemists were “sick”, compared to 8% of the controls ($p < 0.001$). The nature of the illnesses was not mentioned; however, they were listed as being associated with temporary disability to work related to pathology of the pregnancy. No chemicals were identified in the study other than acetylene-vinyl acetate. Other materials that the female workers may have been exposed to were not mentioned or quantified. Additional variables that could have affected the results (e.g., age, number of years on the job, smoking, nutritional or social status) were not examined. Since the workers presumably were also exposed to vinyl acetate as well as acetylene, no causative relationship between exposure to acetylene and reproductive toxicity can be identified from this study. Due to the aforementioned limitations, this study cannot be considered valid. No other studies linking exposure of acetylene to any kind of reproductive concerns have been published over a long history of use.

Further Testing Would Be Hazardous

If further studies on acetylene were undertaken, they would provide little additional useful knowledge of the hazards of this substance without leading to study conditions (very high air concentrations) that would present a serious explosion hazard to animals and people. Reproductive and developmental testing would require inhalation chambers that contained greater than the lower explosive limit concentration (25,000 ppm) of acetylene in order to demonstrate a toxicological effect. These concentrations would have to be maintained for several hours per day (and confirmed by analytical monitoring) for a number of days. Even if these conditions were achievable without incident, the data presented above indicate that the only manifestation of toxicity that would be observed is narcosis, asphyxiation of test animals, and pulmonary irritation.

4.4.6 Summary/Test Plan for Mammalian Toxicity

Acute and repeated dose studies that have been performed with acetylene in humans and animals and the repeated dose study with a related material (methylacetylene) adequately fill the acute and repeated dose endpoints. The bacterial mutagenicity tests that have been performed with acetylene and methylacetylene adequately characterize the potential for acetylene to cause mutagenicity. Therefore, no new testing of these three endpoints is planned. It is not considered necessary to perform chromosomal aberration or reproductive/developmental toxicity tests in animals to characterize these endpoints since mutagenicity studies indicate a lack of mutations, such toxicity has not surfaced after over a century of use of the material, acetylene is minimally toxic to mammals (except at exceedingly high doses or concentrations which are not likely to be present in the workplace), acetylene is rapidly excreted from the lungs without metabolism, performance of such studies would be extremely hazardous. Since the predominant use is as a closed system intermediate with little potential for exposure and the other use is as a fuel for oxyacetylene welding where the acetylene is consumed, potential exposure is severely limited.

5.0 Summary

Table 5 at the end of this section provides a summary of the available data for acetylene.

Physical Properties

Measured data are available for all required physical property endpoints except vapor pressure and partition coefficient. Acetylene has been a commercial industrial chemical for many decades and was well studied long ago with respect to its physical properties. Although the measured data were not determined by current guideline methods and testing predicated good laboratory practices, the data should be accepted as reliable. The EPIWIN Kowwin-generated value for partition coefficient and the calculated value for vapor pressure is also considered reliable and accurate. No new testing is proposed.

Environmental Fate Properties

Estimated values are available for the hydroxyl radical induced photolysis rate constant and atmospheric half-life, Henry's Law Constant, soil sediment partition coefficient, and Fugacity Level III environmental transport parameters. These values indicate that acetylene has a very strong tendency to partition to the atmosphere, where it undergoes photodegradation. The small amounts of material present in the hydrosphere can be oxidized and reduced by sediment bacteria and are estimated by EPIWIN Biowin to be readily biodegradable. Although a measured hydrolysis rate constant is not available for acetylene, the material is soluble and theoretically stable in water, and any material present in water will rapidly evaporate. Therefore, water stability testing is not proposed.

Aquatic Toxicity

Since the material is a gas, it is not expected to be present in environmental waters at any of the concentrations shown to be toxic to fish or estimated by EPIWIN to be toxic to aquatic species. The utility of tests that have been performed is questionable since experimental details were not available. The hazard in conducting additional tests is not worth the risk, especially since guideline tests will not adequately simulate environmental conditions in which acetylene will remain in the atmosphere. No additional testing is proposed.

Mammalian Toxicity

Acute and repeated dose studies and bacterial mutagenicity tests that have been performed with acetylene and the related material methylacetylene adequately fill these endpoints. Therefore, no new testing of these three endpoints is proposed. No chromosome aberration or reproductive or developmental toxicity testing is proposed, due to the history, nature and uses of the material.

Table 5. Summary of Data Availability for Acetylene (CAS No. 74-86-2)

<i>Endpoint</i>	<i>Availability of Data</i>	<i>Proposed Testing</i>
PHYS/CHEM PROPERTIES		
Melting Point	A	None
Boiling Point	A	None
Vapor Pressure	A	None
Partition Coefficient	A	None
Water Solubility	A	None
ENVIRONMENTAL FATE		
Photodegradation	A	None
Stability in Water	NA	None
Biodegradation	NA	None
Transport between Environmental Compartments (Fugacity)	A	None
ECOTOXICITY		
Acute Toxicity to Fish	A	None
Acute Toxicity to Aquatic Invertebrates	A	None
Acute Toxicity to Aquatic Plants	A	None
HUMAN HEALTH		
Acute Toxicity	A	None
Repeated Dose Toxicity	R	None
Genetic Toxicity-Mutagenicity	R	None
Genetic Toxicity-Chromosomal Aberration	A	None
Reproductive Toxicity	A	None
Developmental Toxicity	A	None

A = Adequate data exists.

R = Read across.

NA = Information is presented which highlights the lack of relevance of data for the endpoint and is therefore, not applicable.

6.0 References

American Conference of Governmental Industrial Hygienists (ACIGH). 2001. Documentation of the threshold limit values and biological exposure indices, 7th Ed.

American Conference of Governmental Industrial Hygienists (ACIGH). 2003. TLVs and BEIs Handbook.

Adriani J. 1962. Chemistry and Physics of Anesthetics, 2nd Ed., Springfield, IL: Charles C Thomas.

Adriani J. 1952. The Pharmacology of Anesthetic Drugs. A Syllabus for Students and Clinicians, 3rd Edition. Springfield, IL: Charles C Thomas.

Araki A, Noguchi T, Kato F and Matsushima T. 1994. Improved method for mutagenicity testing of gaseous compounds by using a gas sampling bag. Mut Res 307: 335-344.

Carreün. T. 2000. Aliphatic Hydrocarbons. Patty's Toxicology, 5th Edition. Clayton GD and Clayton FE (Eds). Vol. 4, p.119.

Clayton GD and Clayton FE. (Eds.) 1981-2. Patty's Industrial Hygiene and Toxicology, 3rd Ed., Volume 2A, 2B, 2C. New York: John Wiley & Sons, Inc. p 3212.

Daubert TE. and Danner RP. 1989. Physical and Thermodynamic Properties of Pure Chemicals Data Compilation, Washington, D.C.: Taylor and Francis.

Davidson BM. 1925. Studies of intoxication. II. The action of acetylene. J Pharm Exper Ther 25: 119-135.

EPIWIN AOP (v1.90).

EPIWIN ECOSAR (v0.99g).

EPIWIN HENRY (v3.10).

EPIWIN HYDROWIN (v1.67).

EPIWIN Level III Fugacity modeling program.

Franken H and Miklos L. 1933. Zentralb Gynaekol 42: 2493 - 2498, abstract cited in a literature search conducted by the Haskell Laboratory, on June 18, 1999.

Grayson M, (Ed.). Kirk-Othmer Encyclopedia of Chemical Technology, 3rd Ed., , New York, John Wiley and Sons, 1978.

Hansch C, Leo Aand Hoekman D. 1995. Exploring QSAR - Hydrophobic, Electronic, and Steric Constants. Washington, DC: American Chemical Society.

Hansen ES. 1991. Am J Ind Med 20:401-409.

Heymans C and Bouckaert JJ. 1925. CR Social Biol (Paris) 93:1036 - 1037, as described in ACGIH, 1991, Documentation of TLVs and BEIs (6th Ed).

Horn HJ, Weir RJ Jr. and Reese WH. 1957. Inhalation toxicology of methylacetylene. Arch Ind Health 15: 20-26.

Hughes TJ, Sparacino C and Frazier S. 1984. Validation of chemical and biological techniques for evaluation of vapors in ambient air/mutagenicity testing of twelve (12) vapor-phase compounds. EPA Report Number 68-02-3170, NTIS Publication PB84-164219.

Jibelian G, Mitchell RR and Overland ES. 1981. Influence of hematocrit and temperature on solubility of acetylene and dimethyl ether. J Appl Physiol: Respirat Environ Exercise Physiol 51(5): 1357 – 1361.

Jones AR. 1960. Arch Environ Health. 5:417-422.

Kirk-Othmer Encyclopedia of Chemical Technology. John Wiley & Sons, Inc. New York, 1995.

Klimisch HJ, Andreae M and Tillmann U. 1997. A systematic approach for evaluating the quality of experimental toxicological and ecotoxicological data. Reg Tox Pharm 25:1-5.

Laesen J, Loechner U, and Toki G. 2001. CEH (Chemical and Economics Handbook) Product Review.

Lide DR. (Ed.). 1992-1993.,CRC Handbook of Chemistry and Physics. 73rd ed. Boca Raton, FL: CRC Press Inc., p. 3-26.

McAuliffe C. 1966. J Phys Chem 70: 1267-75.

Morris PD et al. 1986. J Natl Cancer Inst. 76(6):987-994.

National Fire Protection Association. 1997. Fire Protection Guide to Hazardous Materials, 12th Ed., Quincy, MA. P 325.

Newhouse ML et al. 1988. Br J Ind Med 45:63-69.

Patterson RM et al. 1976. NTIS Report No. PB-258353.

Riboli E et al. 1988. Scand J Environ Health 9:455-462.

Riggs LK. 1925. The physiologic properties of some unsaturated hydrocarbons. Proc Soc Exp Biol Med 22: 269-270.

Rohm and Haas Company. 1980. OTS0518103 and OTS0518118 (TSCATS/402048, 402078).

Schrikker ACM, de Vries WR, Zwart A and Luijendijk SCM. 1989. The sloping alveolar plateau of tracer gases washed out from mixed venous blood in man. *Pflügers Arch* 413: 516 -422.

Siemiatycki et al. 1982. *Teratog Carcinog Mutagen* 2(2): 169-177. No first initial was provided in secondary reference.

Talakina EI et al. 1977. *Gig Tr Prof Zabol* 3:46-47.

Waxweiler RJ. 1981. *Environ Health Perspect* 42: 51-56.

Williams AR et al. 1989. *Cancer Res.* 49:4038-4041.